


ACCESSORI / ACCESSORIES / ZUBEHÖR

	6402-06-000 Ottica 120° trasparente Transparent optic 120° Transparente Abdeckung 120°	Materiale Material Material	Policarbonato Polycarbonate Polycarbonat
	6402-07-000 Ottica 120° satinata Satinated optic 120° Opale Abdeckung 120°	Materiale Material Material	Policarbonato Polycarbonate Polycarbonat
	6402-08-000 Ottica 60° trasparente Transparent optic 60° Transparente Abdeckung 60°	Materiale Material Material	Policarbonato Polycarbonate Polycarbonat
	IP40 6404-50-28 6404-50-27 6404-50-26 IP65 6404-50-21 6404-50-20 6404-50-19 Supporto in ottone cromato opaco Brass bracket matt chromed Halter für Profil aus Messing, matt verchromt	Materiale Material Material	Ottone Brass Messing

ACCESSORI IP65 / ACCESSORIES IP65 / ZUBEHÖR IP65

	6404-50-017 Giunto per connessioni IP68 a due vie Joint for connection IP68 with two exits Verbindungsbox IP 68 mit zwei Ausgängen	Materiale Material Material	PA66
	6404-50-023 Giunto per connessioni IP68 a quattro vie Joint for connection IP68 with four exits Verbindungsbox IP 68 mit vier Ausgängen	Materiale Material Material	PA66



PROFILE



FABAS LUCE S.p.A.
Via Luigi Talamoni, 75
20861 BRUGHERIO (MB) Italy
Tel. 0039 039 214 22 06
0039 039 89 06 91
Fax 0039 039 214 22 08
www.fabasluce.it
info@fabasluce.it

FABAS LUCE GmbH
ATILED SHOWROOM
Franz Volk Strasse 5a
D - 77652 Offenburg
Tel. +49(0) 781 125 59 932
www.atiled.it
atiled.germany@fabasluce.com





IP40

23W/m



CE



6704 SHARON PLUS

Profilo / Profile / Profil

Struttura/Frame/Rahmen

Alluminio/Aluminium/Aluminium

Optica/Optic/Linse

120° / 60°

Driver/Driver/Treiber

Escluso/Excluded/Nicht inklusiv

Alimentazione/Power supply/Transformator

24V DC

Taglio/Cut/Schneidbar

10 cm

Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom	23W/m
Lumen	2400 Warm white - 2600 Natural white
Lm/W@85°C	110 Warm white - 115 Natural white
CRI TYP	85
Tipo di raffreddamento	Passivo
Type of cooling/Kühlungsart	Passive/Passiv
Temperatura ambiente di funzionamento	-20° + 50° C
Operating ambient temp.	
Betriebsumgebungstemperatur	
Numero LED/LED number/Anzahl LED	70 LED/m
Tipo di garanzia	Garanzia 5 anni
Warranty type/Garantie Typ	5 years/5 Jahre

23W/m



CE



6404 SHARON RGB

Profilo / Profile / Profil

Struttura/Frame/Rahmen

Alluminio/Aluminium/Aluminium

Optica/Optic/Linse

120° / 60°

Driver/Driver/Treiber

Escluso/Excluded/Nicht inklusiv

Alimentazione/Power supply/Transformator

24V DC

Taglio/Cut/Schneidbar

10 cm

Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom	23W/m
Tipo di raffreddamento	Passivo
Type of cooling/Kühlungsart	Passive/Passiv
Temperatura ambiente di funzionamento	-20° + 50° C
Operating ambient temp.	
Betriebsumgebungstemperatur	
Numero LED/LED number/Anzahl LED	70 LED/m
Tipo di garanzia	Garanzia 5 anni
Warranty type/Garantie Typ	5 years/5 Jahre

10W/m



CE



6414 SABINE

Profilo / Profile / Profil

Struttura/Frame/Rahmen

Alluminio/Aluminium/Aluminium

Optica/Optic/Linse

120° / 60°

Driver/Driver/Treiber

Escluso/Excluded/Nicht inklusiv

Alimentazione/Power supply/Transformator

24V DC

Taglio/Cut/Schneidbar

10 cm

Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom	10W/m
Lumen	1000 Warm white - 1050 Natural white
Lm/W@85°C	105 Warm white - 110 Natural white
CRI TYP	85
Tipo di raffreddamento	Passivo
Type of cooling/Kühlungsart	Passive/Passiv
Temperatura ambiente di funzionamento	-20° + 50° C
Operating ambient temp.	
Betriebsumgebungstemperatur	
Numero LED/LED number/Anzahl LED	140 LED/m
Tipo di garanzia	Garanzia 5 anni
Warranty type/Garantie Typ	5 years/5 Jahre

5W/m



CE



6427 EBAN

Profilo / Profile / Profil

Struttura/Frame/Rahmen

Alluminio/Aluminium/Aluminium

Optica/Optic/Linse

120° / 60°

Driver/Driver/Treiber

Escluso/Excluded/Nicht inklusiv

Alimentazione/Power supply/Transformator

24V DC

Taglio/Cut/Schneidbar

10 cm

Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom	5W/m
Lumen	490 Warm white - 520 Natural white
Lm/W@85°C	105 Warm white - 110 Natural white
CRI TYP	85
Tipo di raffreddamento	Passivo
Type of cooling/Kühlungsart	Passive/Passiv
Temperatura ambiente di funzionamento	-20° + 50° C
Operating ambient temp.	
Betriebsumgebungstemperatur	
Numero LED/LED number/Anzahl LED	70 LED/m
Tipo di garanzia	Garanzia 5 anni
Warranty type/Garantie Typ	5 years/5 Jahre



IP65

23W/m



CE



6704 SHARON PLUS

Profilo / Profile / Profil

Struttura/Frame/Rahmen

Alluminio/Aluminium/Aluminium

Optica/Optic/Linse

120° / 60°

Driver/Driver/Treiber

Escluso/Excluded/Nicht inklusiv

Alimentazione/Power supply/Transformator

24V DC

Taglio/Cut/Schneidbar

10 cm

Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom	23W/m
Lumen	2400 Warm white - 2600 Natural white
Lm/W@85°C	110 Warm white - 115 Natural white
CRI TYP	85
Tipo di raffreddamento	Passivo
Type of cooling/Kühlungsart	Passive/Passiv
Temperatura ambiente di funzionamento	-20° + 50° C
Operating ambient temp.	
Betriebsumgebungstemperatur	
Numero LED/LED number/Anzahl LED	70 LED/m
Tipo di garanzia	Garanzia 5 anni
Warranty type/Garantie Typ	5 years/5 Jahre

23W/m



CE



6404 SHARON RGB

Profilo / Profile / Profil

Struttura/Frame/Rahmen

Alluminio/Aluminium/Aluminium

Optica/Optic/Linse

120° / 60°

Driver/Driver/Treiber

Escluso/Excluded/Nicht inklusiv

Alimentazione/Power supply/Transformator

24V DC

Taglio/Cut/Schneidbar

10 cm

Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom	23W/m
Tipo di raffreddamento	Passivo
Type of cooling/Kühlungsart	Passive/Passiv
Temperatura ambiente di funzionamento	-20° + 50° C
Operating ambient temp.	
Betriebsumgebungstemperatur	
Numero LED/LED number/Anzahl LED	70 LED/m
Tipo di garanzia	Garanzia 5 anni
Warranty type/Garantie Typ	5 years/5 Jahre

10W/m



CE



6414 SABINE

Profilo / Profile / Profil

Struttura/Frame/Rahmen

Alluminio/Aluminium/Aluminium

Optica/Optic/Linse

120° / 60°

Driver/Driver/Treiber

Escluso/Excluded/Nicht inklusiv

Alimentazione/Power supply/Transformator

24V DC

Taglio/Cut/Schneidbar

10 cm

Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom	10W/m
Lumen	1000 Warm white - 1050 Natural white
Lm/W@85°C	105 Warm white - 110 Natural white
CRI TYP	85
Tipo di raffreddamento	Passivo
Type of cooling/Kühlungsart	Passive/Passiv
Temperatura ambiente di funzionamento	-20° + 50° C
Operating ambient temp.	
Betriebsumgebungstemperatur	
Numero LED/LED number/Anzahl LED	140 LED/m
Tipo di garanzia	Garanzia 5 anni
Warranty type/Garantie Typ	5 years/5 Jahre